

Specifications



Photo is representative

Eaton XTCE095F00TD

Eaton XT IEC contactor, 95A, 24-27 Vdc, 0NO-0NC, 95A, Frame F, 90 mm, 40, 50, 100, 125 hp (3PH @200, 230, 460, 575 V), Three-pole, Non-reversing, XT IEC series, Screw terminals, Full voltage non-reversing contactor

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE095F00TD
EAN	4015082395100
PRODUCT LENGTH/DEPTH	6.2992126 in
PRODUCT HEIGHT	6.69291339 in
PRODUCT WIDTH	4.37007874 in
PRODUCT WEIGHT	0.61729433 lb
CERTIFICATIONS	UL Listed CSA Certified



Powering Business Worldwide

Product specifications

AMPERAGE RATING	95A
HP RATING - MAX	40, 50, 100, 125 hp (3PH @200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
TERMINALS	Screw terminals
COIL VOLTAGE	24-27 Vdc
CONTACT CONFIGURATION	0 NO, 0 NC
CONTINUOUS AMPERE RATING	95 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE095F00TD
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.