Specifications



Photo is representative

Eaton XTCE150G00C

Eaton XT IEC contactor, 150A, 480 Vac 50 Hz, 500 Vac 60 Hz, 0NO-0NC, 150A, Frame G, 90 mm, 50-60 Hz, 10, 25, 30/ 40, 60, 125, 125 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVNR

General specifications	
PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE150G00C
UPC	782116487158
PRODUCT LENGTH/DEPTH	6.732 in
PRODUCT HEIGHT	6.89 in
PRODUCT WIDTH	3.583 in
PRODUCT WEIGHT	4.8 lb
CERTIFICATIONS	UL Listed EN 60947 CSA Certified IEC 60947

Powering Business Worldwide

Product specifications

AMPERAGE RATING	150A
HP RATING - MAX	10, 25, 30/ 40, 60, 125, 125 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	50-60 Hz
CONNECTION	Screw connection
FRAME SIZE	90 mm
TERMINALS	Screw terminals
COIL VOLTAGE	480-500 Vac, 50/60 Hz
CONTACT CONFIGURATION	0 NO, 0 NC
CONTINUOUS AMPERE RATING	150 A
FRAME	R
SERIES	XT IEC
OPERATION	Non-reversing

Resources

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE150G00C

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.