YTU321R321R, 1-piece Heavy-Wall Aluminum Tap Connector

By Burndy
Catalog # YTU321R321R



1-piece heavy wall AL compression tap connector for secondary service drop and transformer tap to primary or secondary, Die index: M.

General

Catalog Number	YTU321R321R
Connector Type	Tap
Die Index Run Side	M
Die Index Tap Side	M
Material	Aluminum Alloy
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
UPC	781810155806
UPC 12 Digit	7818101558066

Dimensions

Dimension - B Length inch	2.71 in
Dimension - Height fraction	4-1/3 in
Dimension - Height inch	4.36 in
Dimension - L Length Overall mm	222 mm
Dimension - Length Overall inch	8.75 in

Conductor Related

Conductor - ACSR Str Run	336.4 kcmil, 300 kcmil
Conductor - ACSR Str Run Range	300 kcmil-336.4 kcmil
Conductor - ACSR Str Tap	336.4 kcmil(18-1 STR), 300 kcmil(26-7 STR)
Conductor - ACSR Str Tap Range	336.4 kcmil(18-1 STR)-300 kcmil(26-7 STR)
Conductor - AL Str Run	350 kcmil, 336.4 kcmil
Conductor - AL Str Run Range	336.4 kcmil-350 kcmil
Conductor - AL Str Tap	350 kcmil(19,37 STR), 336.4 kcmil(19,37 STR)
Conductor - AL Str Tap Range	336.4 kcmil(19,37 STR)-350 kcmil(19,37 STR)
Conductor - Copper Str Run	350 kcmil
Conductor - Copper Str Tap	350 kcmil(19,37 STR)

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Product Assets

Catalogs - Full Line BURNDY Catalog
Catalogs - Section H - Overhead Distribution
Customer Notices - Prop 65 Notice
Product Cross Section Image(s) - BUR_YTU-R-R_LineArt
Sales Drawings - SD031286

©2024 Hubbell Incorporated. All rights reserved.
BRDY_CA-YTU321R321R-SPEC-EN | REV 6/2024