

Eaton C25DNF340C-GL

Catalog Number: C25DNF340C-GL

Eaton definite purpose contactor, Mounting plate, Quick, Quick connect (side-by-side), 277 Vac, 60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, Contactor, Three-pole, Global listed, D1, Box lugs (posidrive setscrew)



General specifications

Product Name	Catalog Number
Eaton definite purpose contactor	C25DNF340C-GL
UPC	Product Length/Depth
786685699301	3.35 in
Product Height	Product Width
3.75 in	2.4 in
Product Weight	Warranty
1.19 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
	1 year
Compliances	Certifications
CE Marked	UL Listed file E1491 (Guide Number NLDX2)
RoHS Compliant	CSA Certified
	UL Recognized

Product specifications

Accessories

Mounting plate

Amperage Rating

40A

Number Of Poles

Three-pole

Options

Global listed

Type

Non-reversing

Auxiliary contacts

Quick connect (side-by-side)

Coil

380-415 Vac, 50 Hz

Coil voltage

440-480 Vac, 50/60 Hz

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

40 A

Model

Contactor

Resistive load

50 A

Series

D1

Terminals

Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)

Connection

Quick

Resources

Drawings

[C25DNF3 3D Model Xchange](#)

[C25DNF3 2D Drawing Xchange](#)

[C25DNF3 3D Inventor](#)

[C25DNF3 AutoCAD 2D Footprint \(mm\)](#)

[C25DNF3 2D PDF](#)

[C25DNF3 AutoCAD 2D Footprint](#)

Specifications and datasheets

[Eaton Specification Sheet - C25DNF340C-GL](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia