Low Voltage Distribution Transformer - Three Phase, 208Δ - 208Y/120V, 15kVA, Shielded

By Acme Electric
Catalog # T3015K0064BS



208Δ Primary Volts - 208Y/120 Secondary Volts - 3Ø.

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

ANFC Taps	2
BNFC Taps	2
Catalog Number	T3015K0064BS
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	208Δ
Product Category	Dry Type Distribution Transformer
Secondary Voltage	208Y/120 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503092712
Winding Material	AL
kVA	15

Dimensions

Dimensions	19.37 in x 24.39 in x 25.5 in
Height	25.5 in
Length	19.37 in
Weight	290 lb
Width	24.39 in

Electrical Ratings

Efficiency	97.89%
Frequency Rating	60 Hz
Primary Voltage	208D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Dept of Energy Regulation	Meets or exceed U.S. DOE 10 CFR Part 431
Nema Rating	NEMA 3R
UL Standard	UL 1561

Logistics

Carton Quantity	1
Pallet Quantity	1

Product Assets

Brochures - General Purpose Dry-Type Distribution Transformers
Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers
Customer Notices - Prop65_Cancer
Engineering Drawing - T3015K0064BS
SDS - HCC SDS
Specifications - T3015K0064BS
Terms and Conditions - HCC Terms & Conditions

©2024 Hubbell Incorporated. All rights reserved