Low Voltage Distribution Transformer - Three Phase, 480Δ - 208Y/120V, 9kVA, 316 Stainless Steel

By Acme Electric
Catalog # T2A53310SS



*Representative Image

Low Voltage Distribution Transformer - Three Phase, 480Δ - 208Y/120V, 9kVA, 316 Stainless Steel.

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

BNFC Taps	2
Catalog Number	T2A53310SS
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	480Δ
Product Category	Dry Type Distribution Transformer
Secondary Voltage	208Y/120 V
Taps % Steps	5.0%
UL Insulation Class	180°C
UPC	047503130643
Winding Material	AL
kVA	9

Dimensions

Dimensions	11.52 in x 17.77 in x 14.03 in
Height	14.03 in
Length	11.52 in
Weight	180 lb
Width	17.77 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	480D V

Certifications And Compliance

CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	10

Product Assets

Brochures - General Purpose Dry-Type Distribution Transformers
Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
SDS - HCC SDS
Specifications - T2A53310SS Specification Sheet French
Specifications - T2A53310SS
Terms and Conditions - HCC Terms & Conditions

©2024 Hubbell Incorporated. All rights reserved