HSC112FR, Heat Shrink Tubing, 1.5" ID Min.(Exp.), 0.75" ID Max.(Rec.), 250-500 Flex, PVC, Flame Retardant, Clear, 600V.



By Burndy
Catalog # HSC112FR

Heat Shrink Tubing, 1.5" ID Min.(Exp.), 0.75" ID Max.(Rec.), 250-500 Flex, PVC, Flame Retardant, Clear, 600V.

Features

- Flame Retardant
- Flexible Polyvinylchloride
- 2:1 Shrink Ratio
- 600 Volts

Application

Used on UL Recognized TO 600V

General

Catalog Number	HSC112FR
Connector Type	CLEAR TUBES
EU RoHS Indicator	Yes
Material	Polyvinyl chloride
Sub Brand	VISISHRINK
Trade Name	VISI-SHRINK™
Type	HSC-FR, Fire Retardant
UPC	781810266151

Conductor Related

Conductor Range	250-500 Kcmil
Conductor Size	350kcmil - 750kcmil

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Product Assets

Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Interactive Catalog - BURNDY Full-Line Digital Catalog
Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide
Product Cross Section Image(s) - BUR_HSC100FR_LineArt
Sales Drawings - 50015598
Specifications - HSC112FR Specification Sheet French

©2024 Hubbell Incorporated. All rights reserved