

Specifications



Photo is representative

Eaton XTCE300L22C

Eaton XT IEC contactor, 300A, 250 Vac 40 Hz, 500 Vac 60 Hz, 2NO-2NC, 300A, Frame L, 140 mm, 40-60 Hz, 100, 125, 250, 300 hp (3PH @200, 230, 460, 575 V), Three-pole, Non-reversing, Screw terminals, FVNR

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE300L22C
EAN	4015081363353
PRODUCT LENGTH/DEPTH	7.5 in
PRODUCT HEIGHT	11 in
PRODUCT WIDTH	10 in
PRODUCT WEIGHT	18 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	CSA Certified UL Listed EN 60947 IEC 60947

Product specifications

AMPERAGE RATING	300 A
HP RATING - MAX	100, 125, 250, 300 hp (3PH @200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	40-60 Hz
FRAME SIZE	140 mm
TERMINALS	Screw terminals
COIL VOLTAGE	250-500 Vac, 40/60 Hz
CONTACT CONFIGURATION	2 NO, 2 NC
CONTINUOUS AMPERE RATING	300 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS

[Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - XTCE300L22C](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

