

Specifications



Photo is representative

Eaton XTCE750N22A

Eaton XT IEC contactor, 800A, 110 Vac 40 Hz, 250 Vac 60 Hz, 2NO-2NC, 750A, Frame N, 250 mm, 40-60 Hz, 250, 300, 600, 700 hp (3PH @200, 230, 460, 575 V), Non-reversing, 1102, , Screw terminals, FVNR

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE750N22A
EAN	4015082082222
PRODUCT LENGTH/DEPTH	10.62992126 in
PRODUCT HEIGHT	11.65354331 in
PRODUCT WIDTH	9.13385827 in
PRODUCT WEIGHT	0.5070632 lb
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Powering Business Worldwide

Product specifications

AMPERAGE RATING	800A
HP RATING - MAX	250, 300, 600, 700 hp (3PH @200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	40-60 Hz
FRAME SIZE	250 mm
TERMINALS	Screw terminals
COIL VOLTAGE	110-250 Vac, 40/60 Hz
CONTACT CONFIGURATION	2 NO, 2 NC
CONTINUOUS AMPERE RATING	750 A
SERIES	XT IEC
OPERATION	Non-reversing
RESISTIVE LOAD	1102

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE750N22A
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.