

Eaton 170M5413

Catalog Number: 170M5413

Fuse-link, high speed, 700 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, single indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M5413
	UPC
	051712261180
EAN	Product Length/Depth
5027590457033	168 mm
Product Height	Product Width
80 mm	124 mm
Product Weight	Warranty
538 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

Product specifications

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

700 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

2

Rated voltage AC

690 V

Center-to-center distance of connections

50.4 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I₂T)

405000 at 660 V

Watt losses

95 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

[eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf](#)

[170M5413~Eaton Bussmann series high speed square body fuse](#)

[Bussmann series complete full line catalog no. 1007](#)

Declarations of conformity

[CE Fuse-links for the protection of semiconductor devices, Size 2](#)

[UKCA Fuse-links for the protection of semiconductor devices, Size 2](#)

Pre arc (I2T)

60500

Color

None

Interrupt rating

200 kAIC

Construction size

2

Mounting method

Flush

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

Flush end

B/Visual indicator

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia