Specifications

Eaton C14G40S

Catalog Number: C14G40S

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 40 Amps, 120 kA Breaking capacity, class gG/gL, with striker, compatible with a CH14 Modular fuse holder



General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C14G40S

UPC
051712668378

EAN
5027590494090

Product Length/Depth
51 mm

Product Height
14 mm

Product Width
14 mm

Product Weight
21 g

Warranty
1 year limited

Compliances
RoHS Compliant
CE Marked

Certifications
IEC 60269

Powering Business Worldwide

Product specifications

Type

Fuse

Special features

Striker

Application

for industrial applications
for general purpose use

Amperage Rating

40 A

Fitted with:

Striker

Fuse size

14 x 51 mm

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

500 V

Class

Class C gL/gG

Fuse type

C14G

Utilization category

gG (cable protection/equipment protection)

Fuse indicator

Top fuse status indicator

Watt losses

4.75 W

Connection

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Bussmann series complete full line catalog no. 1007

Declarations of conformity

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Fuse shape

Cylindrical

Voltage type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

Holder

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

500 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia