

Eaton 170M6246

Catalog Number: 170M6246

Fuse-link, high speed, 800 A, AC 1250 V, size 3, 76 x 92 x 139 mm, aR, DIN, IEC, type K indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M6246
	UPC
	051712793612
EAN	Product Length/Depth
5996516018569	168 mm
Product Height	Product Width
76 mm	95 mm
Product Weight	Warranty
961 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

Product specifications

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

800 A

Breaking capacity

100 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

3

Rated voltage AC

1250 V

Center-to-center distance of connections

108 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I²T)

995000 at 1000 V, 1300000 at 1250 V

Watt losses

122 W

Fuse shape

Square body, slotted center bolted tags

Resources

Catalogs

[eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

[170M6246~Eaton Bussmann series high speed square body fuse](#)

Declarations of conformity

[UKCA Fuse-links for the protection of semiconductor devices, Size 3](#)

[CE Fuse-links for the protection of semiconductor devices, Size 3](#)

Pre arc (I2T)

205000

Color

None

Interrupt rating

100 kAIC

Construction size

3

Packaging type

Standard

Voltage rating

1250 V (IEC), 1300 V (UL)

Fuse type

DIN 43653

KN/110 Type K Indicator for Micro

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia