

11PL-C/T/COR/32V-3CCT/
MF15/P/20/1

929003477904



CorePro, LED, PL-C;PL-T, 104 mm, 11 W, Selectable, 3000 K, 3500 K, 4000 K, 1425 lm, 1450 lm, 1500 lm, 30000 hour(s)

CorePro, LED, PL-C;PL-T, 104 mm, 11 W, Selectable, 3000 K, 3500 K, 4000 K, 1425 lm, 1450 lm, 1500 lm, 30000 hour(s), 136.00 lm/W, G24q, Plastic

General Information

Cap-Base	G24q
Nominal lifetime	30,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED

Light Technical

Color Code	3000/3500/4000
Beam Angle (Nom)	120 degree(s)
Luminous Flux	1,425 lm
Color Designation	3000/3500/4000

Correlated Color Temperature (Nom)	Selectable K
Luminous Efficacy (rated) (Nom)	136.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	83
LLMF At End Of Nominal Lifetime (Nom)	70 %
All-in Type	All-in, Multi Color Temperature

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	11 W
Lamp Current (Max)	98 mA
Lamp Current (Min)	39 mA
Wattage Equivalent	32 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120-277 V
UL Type	UL Type B

Temperature

T-Case Maximum (Nom)	75 °C
----------------------	-------

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Frosted
Bulb Material	Plastic
Product Length	104 mm
Bulb Shape	PL-C;PL-T
Net Weight (Piece)	0.105 kg

Approval and Application

Energy Saving Product	Yes
Approval Marks	RoHS compliance
EU RoHS compliant	Yes
Ambient temperature range	-20 to +45 °C


Application Conditions

can it be used in closed luminaires	Yes
Wireless Technology	Not applicable

Product Data


Order product name	11PL-C/T/COR/32V-3CCT/MF15/P/20/1
Full product name	11PL-C/T/COR/32V-3CCT/MF15/P/20/1
Order code	929003477904
Material Nr. (12NC)	929003477904
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677577926
Numerator - Packs per outer box	20
EAN/UPC - Case	50046677577921

Dimensional drawing




Product	D1	D	A1	A2	A3
11PL-C/T/COR/32V-3CCT/MF15/P/20/1	46 mm	54 mm	16 mm	104 mm	119 mm


Photometric data



Spectral Power Distribution Colour - 11PL-C/T/COR/32V-3CCT/MF15/P/20/1




General uniform lighting - 11PL-C/T/COR/32V-3CCT/MF15/P/20/1




Light Distribution Diagram - 11PL-C/T/COR/32V-3CCT/MF15/P/20/1


Lifetime




Life Expectancy Diagram




Lumen Maintenance Diagram - 11PL-C/T/COR/32V-3CCT/MF15/P/20/1



LifetimeVsTc



FailureRate



Lumen Maintenance Diagram - 11PL-C/T/COR/32V-3CCT/
MF15/P/20/1

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	Philips-PL-C-T-COMF-7403978-Ref-929003477904-EPD.pdf	Download 
Installation Instructions	LEDtube-PLCT-CORE-Installation-Guide-INI.pdf	Download 

