Product data sheet

Specifications



End tap box, I-Line Busway, 2500A, 600VAC, 3 phase, 4 wire, integral ground bus, Al, feeder, 10ft, bolted [TAA]

AF2525GETBMB

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	End tap box
Range	I-Line

Complementary

Rated Current	2500 A aluminium
Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	39.38 in (1000.25 mm)
Height	28 in (711.2 mm)
Width	20.88 in (530.35 mm)
Material	Aluminium: busbar
I-LINE Value End	Bolt
Number of Phases	3 phase
For Use with	Busbar trunking 2500 A aluminium
Protection Type	50 percent capacity integral ground bus
Wiring Configuration	4-wire

Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6

Ordering and shipping details

GTIN	785901171553
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	28.0 in (71.1 cm)
Package 1 Width	20.9 in (53.0 cm)
Package 1 Length	49.9 in (126.7 cm)
Package weight(Lbs)	204.999 lb(US) (92.986 kg)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Compliance

Compliance	TAA Compliant BAA Compliant via COTS

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**2 050 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**183 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**51 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**12 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**1 775 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**28 kg CO2 eq.**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Again

Repack and remanufacture

Recyclability potential, in %	**91**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**