Product data sheet

Specifications



D-Frame ATS, ASCO Series 300, open transition, 3 pole, 230A, 208V, Type 1, with 11BE, Cat# D03ATSA30230CGXC,11BE [TAA, BAA, BABA]

PPATS_1020386

Main

Switch Series	ASCO 300 Series
Product or Component Type	Transfer switch
Rated Current	230 A
Number of Phases	Three phase
Number of Poles	3P
Rated Voltage	480 V

Complementary

Neutral Configurations	Solid neutral
Transition Mode	Open
Operation Mode	Automatic
Hot to Hot Transfer Time	< 80 ms
Controller	Group G
Communication Capability	Modbus TCP RS485
Service Entrance Rated	Not service entrance rated
Center Off Position	No
Enclosure Options	UL Type 1
Switch Frame	D-Frame

Ordering and shipping details

GTIN	3606486821749

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	48.0 in (121.9 cm)
Package 1 Width	13.0 in (33 cm)
Package 1 Length	13.0 in (33 cm)
Package weight(Lbs)	125.7 lb(US) (57 kg)

Compliance

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Compliance	TAA Compliant BAA Compliant BABA Compliant BAA Compliant via COTS

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**798 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**359 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**19 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.5 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**402 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**17 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Circularity Profile	**End of Life Information**
Take-back	**No**

Image of product / Alternate images

Alternative

