Product data sheet

Specifications



KIT FLUSH-MOUNTING POUR ATV T3

NSYPTDS3

Product availability: Stock - Normally stocked in distribution facility

Main

Range	PanelSeT
Product or Component Type	Drive flush mounting kit
accessory category	Mounting and fixing accessory
Product Specific Application	Process and utilities
Range compatibility	Altivar variable speed drive ATV630 Altivar variable speed drive ATV930 PanelSeT SF and SM enclosures 23.6 in (600 mm) x 11.8 in (300 mm) PanelSeT S3D enclosure 23.6 in (600 mm) x 11.8 in (300 mm)
compatibility for Altivar Process 630-930, size:	3
Motor power kW	7.5 kW 220/240 V 11 kW 220/240 V 15 kW 380/480 V 18.5 kW 380/480 V 22 kW 380/480 V
Mounting location	1 back of enclosure mounting plate 2 inside enclosure
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic

Complementary

Permanent permissible load	31.5 lb(US) (14.3 kg)
color	Gray RAL 7035)
Height	External: 21.9 in (555 mm) Cut-out: 19.8 in (503 mm)
Width	External: 11.6 in (295 mm) Cut-out: 9.8 in (250 mm)
Depth	Wall-enclosure separation : 0.9 in (22 mm)
Net Weight	5.406 lb(US) (2.452 kg)
Services	Configuration of enclosure pre-drilled back Factory installation drive flush mounting kit

Environment

IP degree of protection	IP55 conforming to IEC 60529

Ordering and shipping details

Category	US1CP4E22277

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Discount Schedule	CP4E
GTIN	3606485433226
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.969 in (5.000 cm)
Package 1 Width	14.567 in (37.000 cm)
Package 1 Length	22.441 in (57.000 cm)
Package weight(Lbs)	5.406 lb(US) (2.452 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	30
Package 2 Height	19.685 in (50.000 cm)
Package 2 Width	39.370 in (100.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	191.802 lb(US) (87.000 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**E893f0a0-d2cc-4011-9425-3873dde70142**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Take-back	**No**