Product data sheet

Specifications



KIT FLUSH-MOUNTING POUR ATV T2

NSYPTDS2

Product availability: Stock - Normally stocked in distribution facility

Main

Range	PanelSeT
Product or Component Type	Drive flush mounting kit
accessory category	Mounting and fixing accessory
Product Specific Application	Process and utilities
Range compatibility	Altivar variable speed drive ATV630 Altivar variable speed drive ATV930 PanelSeT SF and SM enclosures 19.7 in (500 mm) x 11.8 in (300 mm) PanelSeT S3D enclosure 19.7 in (500 mm) x 11.8 in (300 mm)
compatibility for Altivar Process 630-930, size:	2
Motor power kW	5.5 kW 220/240 V 7.5 kW 380/480 V 11 kW
Mounting location	1 back of enclosure mounting plate 2 inside enclosure
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic

Complementary

Permanent permissible load	17.0 lb(US) (7.7 kg)
color	Gray RAL 7035)
Height	External: 16.5 in (420 mm) Cut-out: 14.8 in (375 mm)
Width	External: 10.4 in (265 mm) Cut-out: 8.5 in (215 mm)
Depth	Wall-enclosure separation : 0.9 in (22 mm)
Net Weight	4.237 lb(US) (1.922 kg)
Services	Configuration of enclosure pre-drilled back Factory installation drive flush mounting kit

Environment

IP degree of protection	IP55 conforming to IEC 60529

Ordering and shipping details

Category	US1CP4E22276
Discount Schedule	CP4E

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

GTIN	3606485433219
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.969 in (5.000 cm)
Package 1 Width	11.417 in (29.000 cm)
Package 1 Length	17.323 in (44.000 cm)
Package weight(Lbs)	4.237 lb(US) (1.922 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**E893f0a0-d2cc-4011-9425-3873dde70142**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Take-back	**No**