



contactor relay, 4 NO, 220 V AC, 50/60 Hz, screw terminal, frame size S00

|                                                                                       |                            |
|---------------------------------------------------------------------------------------|----------------------------|
| product brand name                                                                    | SIRIUS                     |
| product designation                                                                   | Auxiliary contactor        |
| product type designation                                                              | 3RH2                       |
| <b>General technical data</b>                                                         |                            |
| size of contactor                                                                     | S00                        |
| product extension auxiliary switch                                                    | Yes                        |
| power loss [W] for rated value of the current without load current share typical      | 1.1 W                      |
| insulation voltage with degree of pollution 3 at AC rated value                       | 690 V                      |
| degree of pollution                                                                   | 3                          |
| surge voltage resistance rated value                                                  | 6 kV                       |
| shock resistance at rectangular impulse                                               |                            |
| • at AC                                                                               | 7,3g / 5 ms, 4,7g / 10 ms  |
| shock resistance with sine pulse                                                      |                            |
| • at AC                                                                               | 11,4g / 5 ms, 7,3g / 10 ms |
| mechanical service life (operating cycles)                                            |                            |
| • of contactor typical                                                                | 30 000 000                 |
| • of the contactor with added electronically optimized auxiliary switch block typical | 5 000 000                  |
| • of the contactor with added auxiliary switch block typical                          | 10 000 000                 |
| reference code according to IEC 81346-2                                               | K                          |
| Substance Prohibitance (Date)                                                         | 10/01/2009                 |
| Weight                                                                                | 0.233 kg                   |
| <b>Ambient conditions</b>                                                             |                            |
| installation altitude at height above sea level maximum                               | 2 000 m                    |
| ambient temperature                                                                   |                            |
| • during operation                                                                    | -25 ... +60 °C             |
| • during storage                                                                      | -55 ... +80 °C             |
| relative humidity minimum                                                             | 10 %                       |
| relative humidity at 55 °C according to IEC 60068-2-30 maximum                        | 95 %                       |
| <b>Environmental footprint</b>                                                        |                            |
| Environmental Product Declaration (EPD)                                               | Yes                        |
| global warming potential [CO2 eq] total                                               | 49.2 kg                    |
| global warming potential [CO2 eq] during manufacturing                                | 1.15 kg                    |
| global warming potential [CO2 eq] during operation                                    | 48.2 kg                    |
| global warming potential [CO2 eq] after end of life                                   | -0.139 kg                  |
| <b>Main circuit</b>                                                                   |                            |
| no-load switching frequency                                                           |                            |
| • at AC                                                                               | 10 000 1/h                 |
| • at DC                                                                               | 10 000 1/h                 |

| Control circuit/ Control                                                       |              |
|--------------------------------------------------------------------------------|--------------|
| type of voltage of the control supply voltage                                  | AC           |
| control supply voltage at AC                                                   |              |
| • at 50 Hz rated value                                                         | 220 V        |
| • at 60 Hz rated value                                                         | 220 V        |
| control supply voltage frequency                                               |              |
| • 1 rated value                                                                | 50 Hz        |
| • 2 rated value                                                                | 60 Hz        |
| operating range factor control supply voltage rated value of magnet coil at AC |              |
| • at 50 Hz                                                                     | 0.8 ... 1.1  |
| • at 60 Hz                                                                     | 0.85 ... 1.1 |
| apparent pick-up power of magnet coil at AC                                    | 33 VA        |
| inductive power factor with closing power of the coil                          | 0.75         |
| apparent holding power of magnet coil at AC                                    | 4.4 VA       |
| inductive power factor with the holding power of the coil                      | 0.25         |
| closing delay                                                                  |              |
| • at AC                                                                        | 8 ... 33 ms  |
| opening delay                                                                  |              |
| • at AC                                                                        | 4 ... 15 ms  |
| arcing time                                                                    | 10 ... 15 ms |
| Auxiliary circuit                                                              |              |
| number of NO contacts for auxiliary contacts                                   | 4            |
| • instantaneous contact                                                        | 4            |
| identification number and letter for switching elements                        | 40 E         |
| operational current at AC-12 maximum                                           | 10 A         |
| operational current at AC-15                                                   |              |
| • at 230 V rated value                                                         | 10 A         |
| • at 400 V rated value                                                         | 3 A          |
| • at 500 V rated value                                                         | 2 A          |
| • at 690 V rated value                                                         | 1 A          |
| operational current at 1 current path at DC-12                                 |              |
| • at 24 V rated value                                                          | 10 A         |
| • at 110 V rated value                                                         | 3 A          |
| • at 220 V rated value                                                         | 1 A          |
| • at 440 V rated value                                                         | 0.3 A        |
| • at 600 V rated value                                                         | 0.15 A       |
| operational current with 2 current paths in series at DC-12                    |              |
| • at 24 V rated value                                                          | 10 A         |
| • at 60 V rated value                                                          | 10 A         |
| • at 110 V rated value                                                         | 4 A          |
| • at 220 V rated value                                                         | 2 A          |
| • at 440 V rated value                                                         | 1.3 A        |
| • at 600 V rated value                                                         | 0.65 A       |
| operational current with 3 current paths in series at DC-12                    |              |
| • at 24 V rated value                                                          | 10 A         |
| • at 60 V rated value                                                          | 10 A         |
| • at 110 V rated value                                                         | 10 A         |
| • at 220 V rated value                                                         | 3.6 A        |
| • at 440 V rated value                                                         | 2.5 A        |
| • at 600 V rated value                                                         | 1.8 A        |
| operating frequency at DC-12 maximum                                           | 1 000 1/h    |
| operational current at 1 current path at DC-13                                 |              |
| • at 24 V rated value                                                          | 10 A         |
| • at 110 V rated value                                                         | 1 A          |
| • at 220 V rated value                                                         | 0.3 A        |
| • at 440 V rated value                                                         | 0.14 A       |
| • at 600 V rated value                                                         | 0.1 A        |
| operational current with 2 current paths in series at DC-13                    |              |
| • at 24 V rated value                                                          | 10 A         |
| • at 60 V rated value                                                          | 3.5 A        |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> <li>• at 220 V rated value</li> <li>• at 440 V rated value</li> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                      | 1.3 A<br>0.9 A<br>0.2 A<br>0.1 A                                                                                                              |
| <b>operational current with 3 current paths in series at DC-13</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                               |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> <li>• at 60 V rated value</li> <li>• at 110 V rated value</li> <li>• at 220 V rated value</li> <li>• at 440 V rated value</li> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                        | 10 A<br>4.7 A<br>3 A<br>1.2 A<br>0.5 A<br>0.26 A                                                                                              |
| <b>operating frequency at DC-13 maximum</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1 000 1/h                                                                                                                                     |
| <b>contact reliability of auxiliary contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 1 faulty switching per 100 million (17 V, 1 mA)                                                                                               |
| <b>UL/CSA ratings</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                               |
| <b>contact rating of auxiliary contacts according to UL</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | A600 / Q600                                                                                                                                   |
| <b>Short-circuit protection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                               |
| design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V                                                                                                                                                                                                                                                                                                                                                                                                                     | C characteristic: 10 A; 0.4 kA                                                                                                                |
| <b>Installation/ mounting/ dimensions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                               |
| <b>mounting position</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface          |
| <b>fastening method</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | screw and snap-on mounting onto 35 mm DIN rail                                                                                                |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 57.5 mm                                                                                                                                       |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 45 mm                                                                                                                                         |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 73 mm                                                                                                                                         |
| <b>required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                               |
| <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul> | 10 mm<br>10 mm<br>10 mm<br>0 mm<br><br>10 mm<br>10 mm<br>6 mm<br>10 mm<br><br>10 mm<br>10 mm<br>10 mm<br>6 mm                                 |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                               |
| type of electrical connection for auxiliary and control circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                               | screw-type terminals                                                                                                                          |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                               |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• for AWG cables for auxiliary contacts</li> </ul>                                                                                                                                                                                                                                                                        | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²<br>2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)<br>2x (20 ... 16), 2x (18 ... 14), 2x 12 |
| <b>Safety related data</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                               |
| <b>product function</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                               |
| <ul style="list-style-type: none"> <li>• positively driven operation according to IEC 60947-5-1</li> <li>• suitable for safety function</li> </ul>                                                                                                                                                                                                                                                                                                                                                                            | Yes<br>Yes                                                                                                                                    |
| suitability for use safety-related switching OFF                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Yes                                                                                                                                           |
| <b>service life maximum</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 20 a                                                                                                                                          |
| <b>proportion of dangerous failures</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                               |
| <ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> <li>• with high demand rate according to SN 31920</li> </ul>                                                                                                                                                                                                                                                                                                                                                                         | 40 %<br>73 %                                                                                                                                  |
| <b>B10 value with high demand rate according to SN 31920</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 1 000 000; With 0.3 x Ie                                                                                                                      |
| <b>failure rate [FIT] with low demand rate according to SN 31920</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 100 FIT                                                                                                                                       |
| ISO 13849                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                               |

|                                                         |                                                  |
|---------------------------------------------------------|--------------------------------------------------|
| device type according to ISO 13849-1                    | 3                                                |
| overdimensioning according to ISO 13849-2 necessary     | Yes                                              |
| IEC 61508                                               |                                                  |
| safety device type according to IEC 61508-2             | Type A                                           |
| Electrical Safety                                       |                                                  |
| protection class IP on the front according to IEC 60529 | IP20                                             |
| touch protection on the front according to IEC 60529    | finger-safe, for vertical contact from the front |

#### Approvals Certificates

##### General Product Approval



[KC](#)



| EMV | Functional Safety | Test Certificates | Marine / Shipping |
|-----|-------------------|-------------------|-------------------|
|-----|-------------------|-------------------|-------------------|



[Type Examination Certificate](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



| Marine / Shipping | other |
|-------------------|-------|
|-------------------|-------|



[Miscellaneous](#)

| other | Railway | Environment |
|-------|---------|-------------|
|-------|---------|-------------|

[Confirmation](#)

[Special Test Certificate](#)



[Environmental Confirmations](#)

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RH2140-1AN20>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RH2140-1AN20>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RH2140-1AN20>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)





[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RH2140-1AN20&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RH2140-1AN20&lang=en)


##### Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RH2140-1AN20/char>

##### Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RH2140-1AN20&objecttype=14&gridview=view1>





last modified:

4/1/2025 