# Product data sheet

Specifications



## 30mm Push Button, Type K, selector switch, 4 position, black knob

9001KS88B

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | Harmony 9001K |
| **Product or Component Type** | Head for selector switch |
| **Device short name** | K |
| **Type of operator** | stay put |
| **Operator profile** | Black standard knob |

## Complementary

| | |
|---|---|
| **Bezel material** | Metal |
| **Mounting diameter** | 1.2 in (30 mm) |
| **Operator position information** | 4 positions |
| **Contacts type and composition** | Without contact block |
| **Mechanical durability** | 0.5 Mcycles |
| **Product compatibility** | 9001KA1 side 1 or 2 |
| **Device presentation** | Basic element |
| **Cap/operator or lens colour** | Black |
| **Operator profile** | Standard handle |
| **Type of operator** | Stay put |
| **Size** | 30 mm |
| **Cam profile** | 8 |

## Environment

| | |
|---|---|
| **IP Degree of Protection** | IP65/IP66 |
| **NEMA degree of protection** | NEMA 3R/6/13 |
| **Product Certifications** | UL listed file E42259 CCN NKCR<br>CE<br>CSA LR24590 class 3211 03 |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CS121426 |
| **Discount Schedule** | 0CS1 |
| **GTIN** | 785901322535 |
| **Returnability** | Yes |
| **Country of origin** | MX |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 2.800 in (7.112 cm) |
| **Package 1 Width** | 2.300 in (5.842 cm) |
| **Package 1 Length** | 2.100 in (5.334 cm) |
| **Package weight(Lbs)** | 5.440 oz (154.221 g) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| SCIP Number | Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d |
| EU RoHS Directive | Compliant By Exemption |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | No |


## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Technical Illustration

**Dimensions**




| Panel Thickness E dim. in. [mm] | Number of Gasket |
|---|---|
| 1/16 [1.6] | 4 |
| 1/8 (3.2) | 3 |
| 3/16 (4.8) | 2 |
| 1/4 (6.4) | 1 |

in.
[mm]

Offer Marketing Illustration

**Product benefits / Features**



Offer Marketing Illustration

**Product benefits / Features**



Image of product / Alternate images

**Alternative**







