

Product data sheet

Specifications



Timing Relay, Type A, pneumatic, on delay, 0.1 to 60 seconds, 15A, 600V, SPDT, timed, 110/120VAC 50/60Hz coil, open

9050AO10EV02

⚠ To be discontinued

⚠ Discontinued on: Mar 31, 2026

⚠ To be end-of-service on: Jun 30, 2026

Product availability: Stock - Normally stocked in distribution facility

Main

Product Range	9050A/H
Product Type	Timer
Timing Mode	On-delay
Timing Range	0.1 s...1 min
Switch Function	SPDT
Coil Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Contact Operation	Time delayed 1 NO + 1 NC
current rating	15 A

Complementary

maximum switching voltage	600 V AC
electrical connection	Screw-clamp terminals
reset response time	29 ms - on-delay 27 ms - off-delay
Mounting Support	Panel

Environment

Ambient Temperature Range - Operational	68...104 °F (20...40 °C)
Certifications	UL Listed CSA
Height	2.6 in (67 mm)
Width	4.02 in (102 mm)
Depth	4.4 in (111 mm)

Ordering and shipping details

Category	US10CP121631
Discount Schedule	0CP1
GTIN	785901864318
Returnability	Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin	MX
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	3.500 in (8.890 cm)
------------------	---------------------

Package 1 Width	4.900 in (12.446 cm)
-----------------	----------------------

Package 1 Length	6.600 in (16.764 cm)
------------------	----------------------

Package weight(Lbs)	27.840 oz (789.250 g)
---------------------	-----------------------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant By Exemption](#)

California proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

Take-back

No