Product data sheet

Specifications



30mm push button, Type SK, control station, START and STOP, 6A inductive at 120VAC, NEMA 4, 4X

9001SKY201

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony 9001KY
Product or Component Type	Control station
Device short name	9001SK
Provided equipment	Label plate START-STOP
Contact block name	KA3 KA1

Complementary

Enclosure/cubicle description	Wall-mounted enclosure 2 cut-outs
AC control voltage 50 HZ	600 V
Enclosure material	Polymeric
Type of Installation	Indoor/outdoor
Control station composition	2 push-buttons 1 NO + 2 NC
AC control voltage 60 HZ	600 V
DC control voltage	125…600 V
Connector Type	Screw clamp connector
[Ue] rated operational voltage	600 V
[Ie] rated operational current AC	10 A
Number of command positions	2
Number of indicator lights	0
Number of push buttons	2
Number of selector switches	0
Number of key switches	0
Number of mushroom-shaped push-buttons	0
Emergency Power Off (EPO)	No
Number of contacts as normally closed contact	2
Number of contacts as normally open contact	1
Number of contacts as change-over contact	0
Housing material	Metal
Housing Colour	Grey
colour of cover	Grey

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

NEMA Degree of Protection	NEMA 4/13
Environmental characteristic	Dust and oil resistant Resistant against immersion in water
Product Certifications	CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR CE
Ambient Air Temperature for Operation	-13…140 °F (-25…60 °C)
Ambient Air Temperature for Storage	-40…158 °F (-40…70 °C)
IP Degree of Protection	IP66

Ordering and shipping details

Category	US10CS121429
Discount Schedule	0CS1
GTIN	785901154181
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.9 in (12.4 cm)
Package 1 Width	6.0 in (15.2 cm)
Package 1 Length	8.8 in (22.4 cm)
Package weight(Lbs)	32.0 oz (907.2 g)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

Take-back	No