

3-Way Lighted Switch, Back and Side-Wire, 20A 120/277V



## Features & Benefits

External screw-pressure-plate back and side wired. Accepts #14 - #10 AWG copper or copper-clad conductors.

Cam controls fast "make" and positive "break" to minimize arcing.

High strength thermoplastic polycarbonate toggle.

Locking support provides resistance to face and back body separation.

Grounding terminal is standard.

Strap nickel-plated steel with integral ground.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

Heavy-gauge one-piece copper alloy contact arm virtually eliminates contact bounce.

Heavy-duty bumper pads for quiet operation.

Back body made of glass-reinforced nylon.

Oversized silver alloy contacts for long life and better heat dissipation.

Shallow design for ease of installation.

Auto-grounded clip assures positive ground.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click [here](#).

## Specifications

### General Info

Product Line	Pass & Seymour	Color	Ivory
Finish	Matte	UPC Number	785007195774
Country Of Origin	Mexico	Material	Thermoplastic
Features	Chemical Resistant	Switch Type	Toggle

---

Number of Switches	1	Application Sector	Commercial, Industrial
--------------------	---	--------------------	------------------------

---

Wall Plate Included	No	Standard	UL 20, FEDSPEC
---------------------	----	----------	----------------

---

Warranty Type	1-Year Limited Warranty	Type	Switch
---------------	-------------------------	------	--------

---

### Dimensions

---

Product Width US	1.32 in	Product Depth US	1.073 in
------------------	---------	------------------	----------

---

Product Height US	3.281 in
-------------------	----------

---

### Listing Agencies / 3rd Party Agencies

---

cULus ListingNumber	140597	cULus Listed	Yes
---------------------	--------	--------------	-----

---

### Technical Information

---

Load Rating	20 A @ 120/277 VAC	Connection Location	Back and Side
-------------	--------------------	---------------------	---------------

---

Terminal Accommodation	#14 AWG - #10 AWG	Number of Gangs	1
------------------------	-------------------	-----------------	---

---

Throw Type	Double Throw	Amperage	20 A
------------	--------------	----------	------

---

Number of Poles	3-Way	Requires Neutral Wire	No
-----------------	-------	-----------------------	----

---

Indoor/Outdoor	Indoor	Mounting Type	Wall Box
----------------	--------	---------------	----------

---

Wire Connection Type	Screw Terminals	Voltage	120 VAC, 277 VAC
----------------------	-----------------	---------	------------------

---

Load Type	CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon
-----------	---

---