

HUBBELL Premise Wiring

ST 2Click, ST, OM1, Beige, 12 Pack

By Hubbell Premise Wiring
Catalog # [FCST62M12](#)



Features

-
-

Application

Interconnect

Performance

- Optical - Insertion loss - 0.5dB (0.35dB typical), 0.75dB max
- Optical - Mating durability - 500 cycles <
- 0.1dB change
- Optical - Multimode return loss - 35dB Typ, 22dB minimum
- Optical - Singlemode return loss - 55dB Typ, 40dB minimum
- Environmental - Operating temperature - 0 °C to +70 °C

General

Adapter Type	SC
Catalog Number	FCST62M12
Color	Beige
Connector Type	SC
EU RoHS Indicator	Yes
Enclosure Type	Various
Environmental Conditions	Indoor
Item Type	ST
Material	Ceramic
Material - Mounting Hardware	Fiber Termination, No Polish
OEM Brand Name	Hubbell Premise Wiring
Repeatability	0.1 dB
Service Life	500 matings
Specifications	<ul style="list-style-type: none">• Cable Type - 900/250 QM• Ferrule Material - Zirconia ceramic, UPC polish• Fiber Type - 62.5QM, OM1
Style	ST 2Click

Sub Brand	OptiChannel
Temperature Rating	OC to 70C
UPC	662620217475

Dimensions

Display Size	2.5 mm
--------------	--------

Electrical Ratings

Connectivity	Fiber Optic Connector
Insertion Loss	0.75 dB Max
Return Loss	26

Conductor Related

Fiber Size	125 Micron
Fiber Type	OM1, MM

Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none">• Telcordia GR-326-CORE• TIA-568-C.3• TIA-604-FOCIS
----------------------	---

Logistics

Carton Quantity	25
-----------------	----

Product Assets

- [Brochures - Fiber Connectivity Product Guide](#)
- [Catalog Page - PREM G3 CatalogPage](#)
- [Catalog Page - PREM G03 Catalog Page](#)
- [Catalogs - Premise Wiring Catalog](#)
- [Sales Drawings - FCST6 - PDF](#)
- [Sell Sheets - FIBERHUBB 2CLICK™ Pre-polished, Non-Adhesive Fiber Connectors](#)
- [Specifications - FCST62M12](#)