

Siemens Low Voltage Talon Meter Sockets Commercial - Talon Meter Sockets PTS- Non Wired Steel are Residential Enclosures Single-Family Metering. Meter Mounting equipment dimensions (L x W x D) IN: 20.0 x 12.0 x 4.5. For transformer-rated applications. Rated 600V (20A) 13 Jaw 16-gauge galv. annealed gray polyester coated steel Ring type split cover enclosure. Hub opening: RX Cl. Plate. Standard 6 and 10 pole, 480V switches available upon request.

| General technical data                        |                  |
|-----------------------------------------------|------------------|
| cable entry type                              | OH/UG            |
| fastening method                              | SURFACE MOUNTING |
| product function note                         |                  |
| number of openings                            | 9                |
| suitability for operation                     | PTS NON WIRED    |
| Electricity                                   |                  |
| ampacity                                      | 20 A             |
| supply voltage frequency rated value 50/60 Hz | No               |
| Model                                         |                  |
| product brand name                            | TALON            |
| product type designation                      | PTS-13           |
| special product feature                       | W/ LOW TEST HAT  |
| Mechanical Design                             |                  |
| design of the terminal strip                  | 13 TERMINALS     |
| General product approval                      |                  |
| certificate of suitability                    | UL               |

last modified:

10/22/2025 

