Product data sheet

Specifications



Discontinued - Service only

Circuit protector, Linergy, thermal magnetic overcurrent, track mount, 10.0A, 125VAC, 65VDC

9080GCB100

Discontinued on: Nov 5, 2025

To be end-of-service on: Dec 30, 2026

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	9080GCB
Product or Component Type	Circuit Protector
Trip Unit Type	Thermal-magnetic
Electrical Connection	Box lugs

Complementary

Protection Type	Overcurrent
Contact operation	Trip-free
Device Application	Industrial Application
Line Rated Current	10 A
Number of Poles	1P
Votlage Rating	65 V DC 125 V AC
Wire Size	AWG 16...AWG 10 copper
Wire stripping length	0.5 in (12.7 mm)
Terminal Tightening Torque	Control circuit 7 lbf.in (0.8 N.m) cage type connector
Terminal Rating	Factory wiring only
Operating Temperature	-22…140 °F (-30…60 °C)
Calibration Temperature	70 °F (21 °C)
Mounting Support	9080GH track 35 mm DIN rail
Height	3.45 in (87.63 mm)
Width	3.15 in (80.01 mm)
Depth	0.5 in (12.7 mm)

Environment

Product Certifications	CE UL recognized E233026 CCN QVNU2 CSA file 025490 class 3211 07
Standards	CSA C22.2 No 235 UL 1077 DIN 57470

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	US10CP521703
Discount Schedule	0CP5
GTIN	785901481010
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.00 in (2.54 cm)
Package 1 Width	3.200 in (8.128 cm)
Package 1 Length	3.700 in (9.398 cm)
Package weight(Lbs)	2.560 oz (72.575 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Height	7.300 in (18.542 cm)
Package 2 Width	12.200 in (30.988 cm)
Package 2 Length	18.300 in (46.482 cm)
Package 2 Weight	16.949 lb(US) (7.688 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	2000
Package 3 Height	40.0 in (101.6 cm)
Package 3 Width	40.0 in (101.6 cm)
Package 3 Length	48.00 in (121.92 cm)
Package 3 Weight	339.0007 lb(US) (153.768 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions

