Product data sheet

Specifications



APC NetShelter Basic Rack PDU, Zero U, 30A, 200/208V, 20 C13 and 4 C19 outlet

AP7541

Product availability: Non-Stock - Not normally stocked in distribution facility

Overview

Presentation	APC Basic Rack PDUs distribute reliable rack power distribution via a single input with multiple output receptacles. Easily mount this vertical PDU in racks or enclosures. It occupies zero U of valuable rack space, which allows space for more equipment in the rack. This vertical PDU does not require additional tools to mount into APC NetShelter Enclosures. Enables a quick recovery from overload events. Packaging Includes PDU, Installation guide, Rack Mounting brackets, Toolless Mounting Kit.
Lead time	Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cord length	9.8 ft (3 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Toolless Mounting Kit

Complementary

Input Voltage	200 V 208 V 230 V
Height	63.7 in (1619 mm)
Width	2.2 in (56 mm)
Output Voltage	200 V 208 V
Depth	1.7 in (44 mm)
Product Weight	12.28 lb(US) (5.57 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	NEMA L6-30P
Mounting Mode	Rack-mounted
Rack units	0U
USB compatible	No
Mounting position	Vertical
Line Rated Current	24 A

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Input current limits	30 A
Load Capacity	4992 VA
Input Frequency	50/60 Hz
Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19

Environment

Product Certifications	cUL Listed METI Denan PSE UL Listed
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1
Ambient air temperature for operation	32…113 °F (0…45 °C)
Relative Humidity	0…95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13…149 °F (-25…65 °C)
Storage Relative Humidity	0…95 %
Storage altitude	0…50000 ft (0…15240 m)

Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304225560
Returnability	No
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	83.5 in (212.1 cm)
Package 1 Width	5.0 in (12.7 cm)
Package 1 Length	6.0 in (15.2 cm)
Package weight(Lbs)	14.29 lb(US) (6.48 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**3 937 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.5 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.5 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**3 913 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.4 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
Halogen content performance	**Product contains halogen above thresholds**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**45**
Circularity Profile	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative

