

# LUTZE Electronic PLTC PVC, Shielded

## Flexible Electronic Cable for Stationary Applications



### Application

- Dual-shielded multi-conductor industrial grade PLTC electronic cable
- Machine tools, machine and plant construction, HVAC technology, assembly and production lines, process instrumentation and controls
- Compliant with NFPA 79 requirements
- PLTC for installation in cable trays

### Characteristics

- Flexible for easy installation
- Easy strip design
- Color coded conductors
- Specially formulated jacket for oil resistance
- Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures
- Premium durability
- Extended temperature range
- Sunlight resistant
- Gas/vapor-tight sheath per UL 13
- Talc and silicone free

### Technical Data

Voltage	300V
Temperature range	-40°C - +105°C
Bending radius min	4 x cable OD
Conductor marking	See tables
Burning behavior	Flame retardant per UL VW-1, FT4
Oil resistance	Oil Res II
Approvals	UL Type PLTC UL Type CM AWM 2464 80C 300V AWM II A/B CE Meets NEC 392, 725, 800 Class I & II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 (PLTC Use Only) UL 13 RoHS, REACH, TSCA

### Construction

- AWG conductor
- Flexible fine wire stranded tinned copper conductors, twisted in pairs
- SR-PVC insulation
- Shielded with foil tape, tinned copper braid and drain wire
- Oil resistant premium PVC jacket
- Gray jacket similar to RAL 7001

Specifications are subject to change without prior notice

Part No.	Description No. of conductors	OD / Ø ca. mm	OD / Ø inches	Weight Lbs/Mft	Copper Lbs/Mft
<b>AWG 22 (19/34)</b>					
A3142202	AWG22/1TP	5.0	0.198	26	12
A3142204	AWG22/2TP	6.6	0.262	42	21
A3142206	AWG22/3TP	6.9	0.273	48	26
A3142208	AWG22/4TP	7.7	0.305	60	31
A3142210	AWG22/5TP	8.3	0.329	69	37
A3142212	AWG22/6TP	9.0	0.354	79	43
A3142216	AWG22/8TP	9.6	0.379	95	54
<b>AWG 20 (19/32)</b>					
A3142002	AWG20/1TP	5.7	0.224	36	18
A3142004	AWG20/2TP	7.6	0.298	58	30
A3142006	AWG20/3TP	8.0	0.313	68	38
A3142008	AWG20/4TP	8.7	0.338	80	47
A3142010	AWG20/5TP	9.3	0.365	93	55
A3142012	AWG20/6TP	10.5	0.409	113	66
A3142016	AWG20/8TP	11.3	0.439	136	84
<b>AWG 18 (19/30)</b>					
A3141802	AWG18/1TP	5.9	0.234	43	27
A3141804	AWG18/2TP	8.4	0.331	72	44
A3141806	AWG18/3TP	8.8	0.348	89	57
A3141808	AWG18/4TP	9.6	0.377	105	71
A3141810	AWG18/5TP	10.9	0.431	134	85
A3141812	AWG18/6TP	11.7	0.463	153	99
A3141816	AWG18/8TP	12.6	0.497	186	125
<b>AWG16 (26/30)</b>					
A3141602	AWG16/1TP	7.3	0.288	61	34
A3141604	AWG16/2TP	10.8	0.425	109	55
A3141606	AWG16/3TP	11.4	0.448	131	72
A3141608	AWG16/4TP	12.3	0.486	159	91
A3141612	AWG16/6TP	14.6	0.573	217	128
A3141616	AWG16/8TP	16.2	0.639	275	162

#### Color Code Table AWG 22 Pair

1-	WH&BK
2-	WH&BN
3-	WH&RD
4-	WH&OG
5-	WH&YE
6-	WH&GN
7-	WH&BU
8-	WH&VT

#### Color Code Table AWG 20, 18 & 16 Pair

1-	BK&RD
2-	BK&WH
3-	BK&GN
4-	BK&BU
5-	BK&BN
6-	BK&YE
7-	BK&OG
8-	RD&GN