



1-Pole Lock Switch, Back and Side-Wire, 20A 120/277V

Features & Benefits

External screw-pressure-plate back and side wired. Accepts #14 - #10 AWG copper or copper-clad conductors.

Cam controls fast "make" and positive "break" to minimize arcing.

High strength thermoplastic polycarbonate toggle.

Locking support provides resistance to face and back body separation.

Grounding terminal is standard.

Strap nickel-plated steel with integral ground.

For covering patents, see www.legrand.us/patents.

Heavy-gauge one-piece copper alloy contact arm virtually eliminates contact bounce.

Heavy-duty bumper pads for quiet operation.

Back body made of glass-reinforced nylon.

Oversized silver alloy contacts for long life and better heat dissipation.

Shallow design for ease of installation.

Auto-ground clip assures positive ground.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click [here](#).

Specifications

General Info

| | | | |
|-------------------|--------------------|-------------|---------------|
| Product Line | Pass & Seymour | Color | Gray |
| Finish | Matte | UPC Number | 785007195613 |
| Country Of Origin | Mexico | Material | Thermoplastic |
| Features | Chemical Resistant | Switch Type | Toggle |

| | | | |
|---------------------|-------------------------|--------------------|------------------------|
| Number of Switches | 1 | Application Sector | Commercial, Industrial |
| Wall Plate Included | No | Standard | UL 498/20, FEDSPEC |
| Warranty Type | 1-Year Limited Warranty | Type | Switch |

Dimensions

| | | | |
|-------------------|----------|------------------|----------|
| Product Width US | 1.32 in | Product Depth US | 1.073 in |
| Product Height US | 2.375 in | | |

Listing Agencies / 3rd Party Agencies

| | | | |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140597 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

Technical Information

| | | | |
|-----------------------|--------------------------------|------------------------|--|
| Load Rating | 20 A @ 120/277 VAC | Connection Location | Back and Side |
| Horsepower Rating | 1 HP @ 120 VAC, 2 HP @ 240 VAC | Terminal Accommodation | #14 AWG - #10 AWG |
| Number of Gangs | 1 | Throw Type | Single Throw |
| Amperage | 20 A | Number of Poles | Single Pole |
| Requires Neutral Wire | No | Indoor/Outdoor | Indoor |
| Mounting Type | Wall Box | Wire Connection Type | Screw Terminals |
| Voltage | 120/277 V | Load Type | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon |