

Specifications



Eaton ISB625A

Eaton Cooper Power series insulated standoff bushing, EPDM rubber, 15/25 kV, Phase to ground: 15.2 kV, AC 1 min: 40 kV, DC 15 min: 78 kV, BIL: 125 kV, Corona: 19 kV, 600 A, Individual box kit

General specifications

PRODUCT NAME	Eaton Cooper Power series insulated standoff bushing
CATALOG NUMBER	ISB625A
UPC	194006001229
PRODUCT LENGTH/DEPTH	5.4 in
PRODUCT HEIGHT	5.6 in
PRODUCT WIDTH	4 in
PRODUCT WEIGHT	1.94 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std 386
PRODUCT TYPE	Insulated standoff bushing



Powering Business Worldwide

Additional Specifications

PACKAGING	Individual box kit
TYPE	Insulated standoff bushing

Electrical Ratings

AC 1 MINUTE VOLTAGE WITHSTAND	40 kV
BASIC IMPULSE LEVEL	125 kV
CURRENT RATING	600 A
MAXIMUM RATING PHASE-TO-GROUND	15.2 kV
STANDARD VOLTAGE CLASS	15/25 kV

Descriptions

MATERIAL	EPDM rubber
-----------------	-------------

Resources

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - ISB625A
	Line installation and protective equipment specifiers guide

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

