


## Specification Sheet

Part Number: FHE



Can be cut to length with scissors, eliminating waste and keeping stock to a minimum.

Available in 9 sizes, for thicknesses from .016" to .512", insuring proper fit.

Grommet, Panel Thickness 0.189"-0.256", PA6, Natural, 82ft/pkg

Article Number 251-21509

Type G51NE

Color Natural (NA)

Quantity Per pack

Product Description HellermannTyton's Flexiform grommet is a unique, continuous wire protection product which fits easily in all shapes and sizes of holes without the aid of tools or adhesives. Flexiform grommet can be used on any type of material including wood, steel, aluminum, plexiglass, and glass.

Short Description Grommet, Panel Thickness 0.189"-0.256", PA6, Natural, 82ft/pkg

Global Part Name G51NE-PA6-NA

Length L (Imperial)	82.0
Variant	Open
Width W (Imperial)	0.39
Width W (Metric)	9.9
Height H (Imperial)	0.252
Height H (Metric)	6.4
Panel Thickness Min (Imperial)	0.19
Panel Thickness Max (Imperial)	0.25
Panel Thickness Min (Metric)	4.8
Panel Thickness Max (Metric)	6.5
Material	Polyamide 6 (PA6)
Material Shortcut	PA6
US MIL SPEC	MS21266-5N
Flammability	UL 94 HB
Halogen Free	Yes

UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-76°F to +203°F (-60°C to +95°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NASM21266
Package Quantity (Imperial)	82
Package Quantity (Metric)	25
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)