

Specification Sheet

Part Number: 556-00230



- LCD user interface for easier setup, diagnostics and adjustments.
- 300 dpi print head for high-resolution printing.
- Label holder included for convenient loading of any size media.
- Small footprint for easy transport to jobsites or around the shop.
- Ethernet ready for wireless network connectivity.
- Print speeds up to 4 in (76.2 mm) per second for fast label production.
- 2 MB flash/8 MB DRAM for accepting large label files that require a lot of data.

|                |            |
|----------------|------------|
| Article Number | 556-00230  |
| Type           | TT230SM    |
| Color          | Black (BK) |
| Quantity Per   | pack       |

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | HellermannTyton's TT230 Series thermal transfer printers are designed for low- to medium-volume printing of thermal transfer labels and ShrinkTrak. They deliver optimal performance not found in other small desktop printers. This lightweight printer offers high speed, precision and flexible printing with the ability to print on most HellermannTyton labels and ShrinkTrak. Used in conjunction with TagPrint Pro, the printers offer error-free printing and seamless operation. |
| Short Description   | TT230SM Thermal Transfer Printer, 300 dpi, Black, 1/pkg                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Global Part Name    | TT230SM-PL-BK                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Length L (Imperial) | 11.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Length L (Metric)   | 279.4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Width W (Imperial)  | 7.95                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Width W (Metric)    | 201                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Height H (Imperial) | 6.81                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Height H (Metric)   | 172.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Depth D (Imperial)  | 11.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Depth D (Metric)    | 279.4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Material            | Plastic (PL)                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Material Shortcut   | PL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

|                              |                                 |
|------------------------------|---------------------------------|
| UV Resistant (Yes/No)        | No                              |
| Operating Temperature        | +40°F to +104°F (+4°C to +40°C) |
| Reach Compliant (Article 33) | Yes                             |
| ROHS Compliant               | Yes                             |
| UL Listed (US and Canada)    | Yes                             |
| Package Quantity (Imperial)  | 1                               |
| Package Quantity (Metric)    | 1                               |
| Customs Number               | 8443321050                      |

7930 N. Faulkner Road, Milwaukee, WI 53224  
 Phone: (800) 537-1512 | Email: corp@htamericas.com