

## Specification Sheet


Part Number: 553-50010

Slide Slit and optional center slits for easy wire insertion.

Smooth surface for clean and legible printing.

Supplied on a ladder style carrier so that markers can be kitted after printing.

A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.



ShrinkTrak Labels, 1-Sided, Unslit, 0.187" (4.74mm), PO-X, White, 1000/box

Article Number

553-50010

Type

HST4.8-1.6WH

Color

White (WH)

Quantity Per

pack

Product Description

HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Short Description

ShrinkTrak Labels, 1-Sided, Unslit, 0.187" (4.74mm), PO-X, White, 1000/box

|                  |                      |
|------------------|----------------------|
| Global Part Name | HST4.8-1.6WH-PO-X-WH |
|------------------|----------------------|

|         |           |
|---------|-----------|
| Variant | Thin-Wall |
|---------|-----------|

|                    |     |
|--------------------|-----|
| Width W (Imperial) | 1.9 |
|--------------------|-----|

|                  |       |
|------------------|-------|
| Width W (Metric) | 48.26 |
|------------------|-------|

|                        |      |
|------------------------|------|
| Thickness T (Imperial) | .003 |
|------------------------|------|

|                      |       |
|----------------------|-------|
| Thickness T (Metric) | .0762 |
|----------------------|-------|

|                     |       |
|---------------------|-------|
| Height H (Imperial) | 0.312 |
|---------------------|-------|

|                   |      |
|-------------------|------|
| Height H (Metric) | 7.92 |
|-------------------|------|

|                         |      |
|-------------------------|------|
| Width of Liner (Metric) | 76.2 |
|-------------------------|------|

|                           |     |
|---------------------------|-----|
| Width of Liner (Imperial) | 3.0 |
|---------------------------|-----|

|                                |       |
|--------------------------------|-------|
| Outside Diameter OD (Imperial) | 0.187 |
|--------------------------------|-------|

|                              |      |
|------------------------------|------|
| Outside Diameter OD (Metric) | 4.74 |
|------------------------------|------|

|                                 |       |
|---------------------------------|-------|
| Outside Diameter Max (Imperial) | 0.187 |
|---------------------------------|-------|

|                               |      |
|-------------------------------|------|
| Outside Diameter Max (Metric) | 4.74 |
|-------------------------------|------|

|                              |       |
|------------------------------|-------|
| Wall Thickness WT (Imperial) | 0.026 |
|------------------------------|-------|

|                            |      |
|----------------------------|------|
| Wall Thickness WT (Metric) | 0.66 |
|----------------------------|------|

|                              |                                                                                |
|------------------------------|--------------------------------------------------------------------------------|
| Material                     | Polyolefin, cross-linked (PO-X)                                                |
| Material Shortcut            | PO-X                                                                           |
| US MIL SPEC                  | SAE-AMS-DTL-23053/5 Class 1 and 3<br>SAE-AS81531<br>MIL-STD-202G Method 215K   |
| Flammability                 | UL 224 VW-1                                                                    |
| Halogen Free                 | No                                                                             |
| UV Resistant (Yes/No)        | No                                                                             |
| Use Conditions               | For Indoor Use Only                                                            |
| Operating Temperature        | -67°F to +275°F (-55°C to +135°C)                                              |
| Reach Compliant (Article 33) | Yes                                                                            |
| ROHS Compliant               | Yes                                                                            |
| Certification/Specification  | SAE - AS81531 SAE - AMS - DTL-23053/5 Class 1 and 3 UL 224 125<br>°C 600V VW-1 |
| Package Quantity (Imperial)  | 1000                                                                           |
| Package Quantity (Metric)    | 1000                                                                           |
| Customs Number               | 3917320000                                                                     |

Labels per Column 1

Labels per Row 1

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)