



Southwire™

PULLING ROPE

Cable pulling rope designed for high breaking strength with low stretch.

- High strength, low stretch
- Excellent resistance to UV rays, chemicals, and abrasions
- Excellent balance
- Factory spliced pulling eye at each end
- Polyester double braid
- 9/16" diameter rope recommended for use with the M3K cable puller
- 5/8" diameter rope recommended for use with the M6K cable puller
- 7/8" diameter rope recommended for use with the XD10 cable puller

HEAVY DUTY
SUPERIOR BREAKING STRENGTH,
LOW STRETCH, UV RESISTANT

COMPOSITE DOUBLE BRAID
DOUBLE BRAID WEAVE PROVIDES
ENHANCED STRENGTH AND
INCREASED PULLING CAPABILITY

READY TO PULL
FACTORY SPLICED PULLING
EYE AT EACH END



MODEL #	STOCK #	DIAMETER (INCHES)	BREAKING STRENGTH (LBS.)	LENGTH (FT.)
P-963	56823501	9/16	16,000	300
P-966	56823601	9/16	16,000	600
P-583	56823701	5/8	18,000	300
P-586	56823901	5/8	18,000	600
P-589	57791201	5/8	18,000	900
P-786	56824001	7/8	31,000	600
P-789	57791301	7/8	31,000	900
P-7812	56824101	7/8	31,000	1200

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

1-855-798-6657 | SOUTHWIRE.COM

©2026 Southwire Company, LLC. All rights reserved.
*Registered Trademark & ™Trademark of Southwire Company, LLC.