

Specification Sheet

Part Number: 558-00501



Continuous Polyester Labels are made with UV stable materials for long outdoor life.

Labels use UV stable permanent ink.

Continuous polyester is provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal trasnfer printing systems.

Adhesive Labels, Solid Color Continuous Roll, 1.0" x 250', UV Stable PET, Red, 250ft/roll

Article Number	558-00501
Type	HT1RDHB250
Color	Red (RD)
Quantity Per	pack
Product Description	Colored continuous rolls offer a high bond adhesive that is sustainable for low surface energy substrates such as the low density plastics on the front of an inverter or powder coat paint surfaces. The adhesive is designed to adhere to textured surfaces without peeling or falling off.
Short Description	Adhesive Labels, Solid Color Continuous Roll, 1.0" x 250', UV Stable PET, Red, 250ft/roll

Global Part Name	HT1RDHB250-840/281-RD
Length L (Imperial)	250.0
Length L (Metric)	76.20
Variant	3.2mil, 50lb bleached kraft paper
Width W (Imperial)	1.0
Width W (Metric)	25.4
Width of Liner (Metric)	25.4
Width of Liner (Imperial)	1.0
Material	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
Material Shortcut	840/281
Adhesive	Acrylic
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)

Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Certification/Specification	IFC 2012 ANSI Standard Z535.4 UL 969 NEC2011 NEC2014 CSA 66956
UL Recognized (US)	Yes
Package Quantity (Imperial)	250
Package Quantity (Metric)	76.20
Customs Number	3919102055
Labels per Column	1
Labels per Row	1

7930 N. Faulkner Road, Milwaukee, WI 53224
 Phone: (800) 537-1512 | Email: corp@htamericas.com