

Specification Sheet

Part Number: 596-00589

Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC® & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

⚠️ WARNING
INVERTER OUTPUT CONNECTION. DO NOT
RELOCATE THIS OVERCURRENT DEVICE.

Pre-printed labels offer significant time and cost savings over high-priced plastic engraved phenolic placards and the lead time of purchased markers.

Solar Label, WARNING INVERTER OUTPUT CONNECTION, 4.125" x .75", VL, Orange, 50/roll

Article Number 596-00589

Type IOCOD

Color Orange (OG)

Quantity Per pack

Product Description

HellermannTyton pre-printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, WARNING INVERTER OUTPUT CONNECTION, 4.125" x .75", VL, Orange, 50/roll

Global Part Name

IOCOD-443/281-OG

Local Order Number 2

Cross Reference = 10 per pack: 596-00668; Metal Solar Placard 5 pack: 596-00836; Spanish version 50 per roll: 596-00826

Width W (Imperial)

4.125

Width W (Metric)

104.6

Thickness T (Imperial)

0.0025

Thickness T (Metric)

64.0

Height H (Imperial)

0.75

Height H (Metric)

19.05

Material

Type 443/281, UV stabilized, flexible white vinyl with clear polyester laminate (443/281)

Material Shortcut

443/281

Adhesive

Acrylic

Halogen Free

No

UV Resistant (Yes/No)

Yes

Use Conditions

For Indoor and Outdoor Use

Adhesive Operating Temperature

-40°F to +174°F (-40°C to +79°C)

Operating Temperature

-40°F to +174°F (-40°C to +79°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant

Yes

Certification/Specification

NEC2014 UL 969

Warranty (US)

Yes

UL Recognized (US)

Yes

Package Quantity (Imperial)

50

Package Quantity (Metric)

50

Customs Number

3919102055

Labels per Column

1

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)