

Specification Sheet

Part Number: 596-00495

Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC® & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

▲ WARNING DUAL POWER SOURCE SECOND SOURCE IS PHOTOVOLTAIC SYSTEM

Pre-printed labels offer significant time and cost savings over high-priced plastic engraved phenolic placards and the lead time of purchased markers.

Solar Label, WARNING DUAL POWER SOURCE...SYSTEM, 4.125" x .75", VL, Orange, 50/roll

Article Number 596-00495

Type WDPSLBL

Color Orange (OG)

Quantity Per pack

Product Description HellermannTyton pre-printed Solar Installation Labels are designed to

meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable

voltage or series data must be printed and displayed.

Short Description Solar Label, WARNING DUAL POWER SOURCE...SYSTEM, 4.125" x

.75", VL, Orange, 50/roll

Global Part Name	WDPSLBL-443/281-OG
Local Order Number 2	Cross Reference = 10 per pack: 596-00665; Metal Solar Placard 5 pack: 596-00833
Width W (Imperial)	4.125
Width W (Metric)	104.6
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	0.75
Height H (Metric)	19.05
Material	Type 443/281, UV stabilized, flexible white vinyl with clear polyester laminate (443/281)
Material Shortcut	443/281

Adhesive Acrylic

Halogen Free No

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Adhesive Operating Temperature -40°F to +174°F (-40°C to +79°C)

Operating Temperature -40°F to +174°F (-40°C to +79°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Certification/Specification UL 969 NEC2020 NEC2017 NEC2014 NEC2023

Warranty (US) Yes

UL Recognized (US) Yes

Package Quantity (Imperial) 50

Package Quantity (Metric) 50

Customs Number 3919102055

Labels per Column 1

Labels per Row 1

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions