

Specification Sheet

Part Number: 596-00847

Made with UV stable inks and materials for durability and weather resistance

The labels are supplied with aggressive adhesive to ensure long life

Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections

⚠ WARNING
INVERTER OUTPUT
CONNECTION. DO
NOT RELOCATE
THIS OVERCURRENT
DEVICE.

Solar Label, WARNING INVERTER OUTPUT...OVERCURRENT DEVICE, 2.0" x 1.25", VL, Red, 50/roll

Article Number 596-00847

Type IOCOD11

Color Red (RD)

Quantity Per pack

Product Description Many times common solar label designs are specified even though they might not be required by code. HellermannTyton offers a selection of some of the most commonly requested labels for use on solar installations.

Short Description Solar Label, WARNING INVERTER OUTPUT...OVERCURRENT DEVICE, 2.0" x 1.25", VL, Red, 50/roll

Global Part Name IOCOD11-V-RD

Length L (Imperial)	1.25
Length L (Metric)	31.75
Width W (Imperial)	2.0
Width W (Metric)	50.8
Height H (Imperial)	1.25
Height H (Metric)	31.75
Material	Vinyl (V)
Material Shortcut	V
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant	Yes
Certification/Specification	NEC2011
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.
[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)