

## Specification Sheet

Part Number: 596-73835

White polyester is glossy, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

The printable surface is highly resistant to chemicals and solvents and can withstand long-term UV exposure.



Thermal Transfer Labels, High-Bond Adhesive, 4.0" x 3.0", Polyester, White, 1000/roll

|                |           |
|----------------|-----------|
| Article Number | 596-73835 |
|----------------|-----------|

|      |        |
|------|--------|
| Type | PCP4X3 |
|------|--------|

|       |            |
|-------|------------|
| Color | White (WH) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | For the ultimate in chemical and solvent resistance and long term outdoor durability, the 840 white polyester offers the most aggressive performance features of any other polyester label material. With an initial outdoor life of 7 years, the labels have been tested far beyond the published limits and the acrylic adhesive bonds well to powder coat painted surfaces as well as baked enamel and slightly textured substrates. |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                       |
|-------------------|---------------------------------------------------------------------------------------|
| Short Description | Thermal Transfer Labels, High-Bond Adhesive, 4.0" x 3.0", Polyester, White, 1000/roll |
|-------------------|---------------------------------------------------------------------------------------|

|                                |                                    |
|--------------------------------|------------------------------------|
| Global Part Name               | PCP4X3-840W-WH                     |
| Width W (Imperial)             | 4.0                                |
| Width W (Metric)               | 101.6                              |
| Thickness T (Metric)           | 64.0                               |
| Height H (Imperial)            | 3.0                                |
| Height H (Metric)              | 76.2                               |
| Width of Liner (Metric)        | 106.68                             |
| Width of Liner (Imperial)      | 4.2                                |
| Material                       | Type 840W, Polyester, white (840W) |
| Material Shortcut              | 840W                               |
| Adhesive                       | High Bond Acrylic                  |
| Halogen Free                   | No                                 |
| UV Resistant (Yes/No)          | No                                 |
| Use Conditions                 | For Indoor Use Only                |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C)  |

|                       |                                   |
|-----------------------|-----------------------------------|
| Operating Temperature | -40°F to +300°F (-40°C to +149°C) |
|-----------------------|-----------------------------------|

|                              |     |
|------------------------------|-----|
| Reach Compliant (Article 33) | Yes |
|------------------------------|-----|

|                |     |
|----------------|-----|
| ROHS Compliant | Yes |
|----------------|-----|

|                             |           |
|-----------------------------|-----------|
| Certification/Specification | CSA 66956 |
|-----------------------------|-----------|

|                    |     |
|--------------------|-----|
| UL Recognized (US) | Yes |
|--------------------|-----|

|                             |      |
|-----------------------------|------|
| Package Quantity (Imperial) | 1000 |
|-----------------------------|------|

|                           |      |
|---------------------------|------|
| Package Quantity (Metric) | 1000 |
|---------------------------|------|

|                |            |
|----------------|------------|
| Customs Number | 3919102055 |
|----------------|------------|

|                   |   |
|-------------------|---|
| Labels per Column | 1 |
|-------------------|---|

|                |   |
|----------------|---|
| Labels per Row | 1 |
|----------------|---|

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)