# Product data sheet

Specifications




## 22mm push button, Harmony, yellow control station, trigger action emergency stop, 40mm red mushroom, 1 NC, NEMA 13

XALACS1

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | Harmony XALK |
| **Product or Component Type** | Complete control station |
| **Device short name** | XALK |
| **Product destination** | For XB5 Ø 22 mm control and signalling units |
| **Control station application** | Emergency switching off function |
| **Colour of base of enclosure** | Light grey RAL 7035) |
| **Colour of cover** | Yellow RAL 1021) |

## Complementary

| | |
|---|---|
| **AC control voltage 50 HZ** | 120…600 V |
| **AC control voltage 60 HZ** | 120…600 V |
| **DC control voltage** | 125…600 V |
| **Number of command positions** | 1 |
| **Number of indicator lights** | 0 |
| **Number of push buttons** | 0 |
| **Number of selector switches** | 0 |
| **Number of key switches** | 0 |
| **Number of mushroom-shaped push-buttons** | 1 |
| **Emergency Power Off (EPO)** | No |
| **Number of contacts as normally closed contact** | 1 |
| **Number of contacts as normally open contact** | 0 |
| **Number of contacts as change-over contact** | 0 |
| **Housing material** | Plastic |
| **Housing Colour** | Yellow |
| **colour of cover** | Yellow |

## Environment

| | |
|---|---|
| **Ambient Air Temperature for Storage** | -40…158 °F (-40…70 °C) |
| **Ambient Air Temperature for Operation** | -13…158 °F (-25…70 °C) |
| **IP degree of protection** | IP66 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **NEMA degree of protection** | NEMA 13 |
| **IP Degree of Protection** | IP66 |
| **NEMA Degree of Protection** | NEMA 13 |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US1IPOP22750 |
| **Discount Schedule** | IPOP |
| **GTIN** | 785901554394 |
| **Returnability** | Yes |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 8.200 in (20.828 cm) |
| **Package 1 Width** | 5.400 in (13.716 cm) |
| **Package 1 Length** | 3.300 in (8.382 cm) |
| **Package weight(Lbs)** | 0.500 lb(US) (0.227 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | No |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Take-back | No |

Offer Marketing Illustration

**Product benefits / Features**



Offer Marketing Illustration

**Product benefits / Features**



Image of product / Alternate images

**Alternative**






CM 12
PG 13,5
ISO 20





