Product data sheet

Specifications



additional Input Output module, Altivar, 24V DC, 1 removable spring connector

VW3A3203

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Additional I/O module
Range Compatibility	Altivar Process ATV600 Altivar Machine ATV340 Altivar Process ATV900 Easy Altivar 610
Input/Output Type	2 analog input configurable voltage, current or probe 6 discrete input 2 discrete output
Analogue input number	2
Analogue input type	AI4, AI5 configurable current 0...20 mA/4...20 mA 0…1 ms 14 bits AI4, AI5 configurable voltage - 10...10 V DC, 24 V max 20 kOhm 0…1 ms 14 bits AI4, AI5 configurable PTC, Pt 100, Pt 1000 0…1 ms 14 bits
Discrete output number	2
Discrete output type	DQ11, DQ12) assignable logic 1 ms
Discrete output logic	DQ11, DQ12) negative DQ11, DQ12) positive
Discrete input number	6
Discrete input type	DI11...DI16) programmable 250 Ohm 1 ms
Discrete input logic	Negative DI11...DI16) Positive DI11...DI16)
Discrete input current	2.5 mA

Complementary

Discrete output voltage	24 V DC <= 30 V) assignable logic
Maximum output current	100 mA, assignable logic
Discrete input voltage	24 V DC <= 30 V)programmable
Electrical connection	Removable spring terminal block, 1.5 mm² / AWG 16
Protection type	Reverse polarity protection digital input Short-circuit protection output
Product Weight	1.1 lb(US) (0.5 kg)

Ordering and shipping details

Category	US1CP4E22206
Discount Schedule	CP4E
GTIN	3606480702525
Returnability	Yes
Country of origin	ID

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.559 in (6.500 cm)
Package 1 Width	5.118 in (13.000 cm)
Package 1 Length	7.480 in (19.000 cm)
Package weight(Lbs)	5.679 oz (161.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	7.214 lb(US) (3.272 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**40 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**14 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**26 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.1 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**2a2f2e41-9976-44a1-aaef-cecaebe1de88**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**9**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**