

Data Sheet | Item Number: 734-231

Operating tool; black

<https://www.wago.com/734-231>



Color: ■ black

Technical data

Number of spacings	1 -times
--------------------	----------

Physical data

Depth	50 mm / 1.97 inches
Pin spacing	3.5/3.81 mm

Mechanical data

Suitable	for 734, 2734 Series
----------	----------------------

Material data

Color	black
Material group	I
Insulation material (main housing)	Glass fiber-reinforced polyamide (PA66 GF)
Flammability class per UL94	HB
Fire load	0.015 MJ
Weight	1.2 g

Commercial data

Product Group	3 (Multi Conn. System)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454272173
Customs tariff number	82055980000

Product Classification

UNSPSC	27112809
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-44-04-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

Approvals for marine applications



Approval	Standard	Certificate Name
LR Lloyds Register	IEC 61984	96/20035 (E5)

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 734-231

CAD/CAE-Data

CAD data
2D/3D Models 734-231

Installation Notes



Conductor termination parallel to CAGE CLAMP® actuation



Inserting a conductor via operating lever.