

HSB110H9PF5, Heat Shrink Tubing, 1.1" ID Min.(Exp.), 0.4" ID Max.(Rec.), 1-3/0 AWG, Heavy Wall, Black, Shrink ratio-3:1, 1500V

By Burndy

Catalog # [HSB110H9PF5](#)

Thick wall heat shrink tubing



Features

- Heavy Wall Heat Shrink Tubing
- Shrink Ratio 3:1
- Inside diameter is coated with adhesive sealant to protect against moisture and corrosion
- Rated to 1500 V
- UL486D Listed for Direct Burial

Application

For Direct Burial

Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor Size	1AWG - 3/0AWG
Conductor Range	#1 AWG to #3/0 AWG

Configuration

Connector Type

HEAVY WALL TUBES

Current

Voltage Rating 1500 V

Dimensions

Package Length 7 in
Package Width 9 in
Package Weight 10.5 lb.
Package Height 15 in

General

Sub Brand HEAT SHRINK
Type HS-H-PF, Heavy Wall, Flame
Retardant
Material Cross-linked Polyolefin
UPC 781810214831

Logistics

Minimum Pack Quantity 1
Number of Pieces in Package 5
Carton Quantity 125
Pallet Quantity 4500

Product Assets

[Catalog \[English\]](#)