

35 kV Class Small Interface Elbow Arrester
(22 kV MCOV)

By Hubbell Power Systems
Catalog # [235ELA27](#)

Small Interface Elbow Arrester, 35kV 22 MCOV



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

Specifications

EU RoHS Indicator No

Current

Duty Cycle	27 kV
Maximum Switching Surge	69.0 kV
Protective Level @ 500A	
Maximum Discharge Voltage	<ul style="list-style-type: none">• 78 kV @ 1.5 kA• 84 kV @ 3 kA• 90 kV @ 5 kA• 99 kV @ 10 kA• 117 kV @ 20 kA• 151.5 kV @ 40 kA
kV Class	35 kV
MCOV	22 kV

Dimensions

Width	3.625 in
Weight	6.500 lb.
Height	13.275 in
Length	10.375 in
Dimensions	10.375 in x 3.625 in x 13.275 in

General

Type	Underground Arresters
Grounding Style	36 in Line Lead
Material	Polymer
Material type	Standard
UPC	096359266679

Logistics

Standard Package	1
Pallet Quantity	64

Operational

Maximum Operating Altitude	6000 ft
----------------------------	---------

Product Assets

[Catalog \[English\]](#)
[Catalog \[English\]](#)
[Installation Manual \[English\]](#)