

HUBBELL Power Systems

15 kV, Load Break Elbow w/ Test Point, Bimetal Contact

By Hubbell Power Systems
Catalog # [215LE44T](#)

Load Break Elbow, 200 Amp, 15 kV, with Test Point, Long Bimetal Contact, Cable Insulation Diameter range = 0.635 - 0.905 inches



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible
- Optional features include test point, integral seal, cold shrink jacket seal kit or shield adapter kit

Specifications

EU RoHS Indicator No

Conductor

Solid or Compacted Conductor 1/0
Stranded or Compressed #1
Conductor

Configuration

With Seal Kit No
With Test Point Yes
Connector Type Bi-Metal

Current

Current Rating 200 A
AC Withstand Voltage (1 min) 34 kV
Corona Extinction (3pC) 11 kV
Basic Impulse Level 95 kV

kV Class 15 kV

Dimensions

Length 7.50 in
Cable Insulation Diameter
Minimum 0.635 in
Cable Insulation Diameter
Maximum 0.905 in
Width 2.875 in
Weight 2.750 lb.
Height 9.00 in
Dimensions 7.50 in x 2.875 in x 9.00 in

General

Material type Standard
PROBELOK® Connectors No
Type 200Amp Load Break
UPC 096359509745
Integral Seal No

Logistics

Standard Package 20
Carton Quantity 20
Pallet Quantity 240

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)