

15 kV Class Elbow Arrester (12.7 kV MCOV)

By Hubbell Power Systems
Catalog # 215ELA15

Deadfront Elbow Arrester.



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

Specifications

EU RoHS Indicator	No
Current	
Maximum Switching Surge	40.0 kV
Protective Level @ 500A	
MCOV	12.7 kV
Duty Cycle	15 kV
Maximum Discharge Voltage	• 45.5 kV @ 1.5 kA • 48.5 kV @ 3 kA • 52 kV @ 5 kA • 57.5 kV @ 10 kA • 67.5 kV @ 20 kA • 87.5 kV @ 40 kA
kV Class	15 kV

Dimensions

Length	10.375 in
Width	2.85 in
Weight	5.200 lb.
Height	12.875 in
Dimensions	10.375 in x 2.85 in x 12.875 in

General

Material type	Standard
Type	Underground Arresters
Grounding Style	36 in Line Lead
Material	Polymer
UPC	096359360490

Logistics

Standard Package	1
Carton Quantity	1
Pallet Quantity	108

Operational

Maximum Operating Altitude	6000 ft
----------------------------	---------

Product Assets

- [Catalog \[English\]](#)
[Catalog \[English\]](#)
[Installation Manual \[English\]](#)