

15 kV Class Elbow Arrester (10.2 kV MCOV)

By Hubbell Power Systems
Catalog # 215ELA12

Deadfront Elbow Arrester.



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

Specifications

EU RoHS Indicator	No
Buy America(n) Qualified	BABA Compliant (All status valid till December 2025)

Current

Maximum Switching Surge	34.0 kV
Protective Level @ 500A	
MCOV	10.2 kV
Duty Cycle	12 kV
Maximum Discharge Voltage	• 39 kV @ 1.5 kA • 41 kV @ 3 kA • 44 kV @ 5 kA • 49 kV @ 10 kA • 57 kV @ 20 kA • 74 kV @ 40 kA
kV Class	15 kV

Dimensions

Length	8.438 in
Width	2.85 in
Weight	3.700 lb.
Height	9.438 in
Dimensions	8.438 in x 2.85 in x 9.438 in

General

Material type	Standard
Type	Underground Arresters
Grounding Style	36 in Line Lead
Material	Polymer
UPC	096359360568

Logistics

Standard Package	1
Pallet Quantity	160

Operational

Maximum Operating Altitude	6000 ft
----------------------------	---------

Product Assets

- [Catalog \[English\]](#)
[Catalog \[English\]](#)
[Installation Manual \[English\]](#)