

15 kV Class Elbow Arrester (8.4 kV MCOV)

By Hubbell Power Systems
Catalog # [215ELA10](#)

Deadfront Elbow Arrester.



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

Specifications

EU RoHS Indicator No

Current

Maximum Switching Surge	24.0 kV
Protective Level @ 500A	
MCOV	8.4 kV
Duty Cycle	10 kV
Maximum Discharge Voltage	• 27 kV @ 1.5 kA • 29.5 kV @ 3 kA • 31.5 kV @ 5 kA • 36 kV @ 10 kA • 41.5 kV @ 20 kA • 53 kV @ 40 kA
kV Class	15 kV

Dimensions

Length	8.500 in
Width	2.85 in
Weight	3.700 lb.
Height	9.500 in
Dimensions	8.500 in x 2.85 in x 9.500 in

General

Material type	Standard
Type	Underground Arresters
Grounding Style	36 in Line Lead
Material	Polymer
UPC	096359266631

Logistics

Standard Package	1
Carton Quantity	1
Pallet Quantity	160

Operational

Maximum Operating Altitude	6000 ft
----------------------------	---------

Product Assets

[Catalog \[English\]](#)
[Catalog \[English\]](#)
[Installation Manual \[English\]](#)