

15 kV Class Elbow Arrester (15.3 kV MCOV)

By Hubbell Power Systems
Catalog # [215ELA18](#)

Deadfront Elbow Arrester.



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

Specifications

EU RoHS Indicator	No
Buy America(n) Qualified	Contact Manufacturer

Current

Duty Cycle	18 kV
Maximum Switching Surge	46.0 kV
Protective Level @ 500A	
Maximum Discharge Voltage	• 52 kV @ 1.5 kA • 56 kV @ 3 kA • 60 kV @ 5 kA • 66 kV @ 10 kA • 78 kV @ 20 kA • 101 kV @ 40 kA

kV Class	15 kV
MCOV	15.3 kV

Dimensions

Width	2.85 in
Weight	5.200 lb.
Height	10.00 in
Length	9.000 in
Dimensions	9.000 in x 2.85 in x 10.00 in

General

Type	Underground Arresters
Grounding Style	36 in Line Lead
Material	Polymer
Material type	Standard
UPC	096359392941

Logistics

Standard Package	1
Pallet Quantity	108

Operational

Maximum Operating Altitude	6000 ft
----------------------------	---------

Product Assets

- [Catalog \[English\]](#)
[Catalog \[English\]](#)
[Installation Manual \[English\]](#)