

15 kV Class Elbow Arrester (5.1 kV MCOV)

By Hubbell Power Systems
Catalog # [215ELA06](#)

Deadfront Elbow Arrester.



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

Specifications

EU RoHS Indicator	No
Buy America(n) Qualified	Contact Manufacturer

Current

Duty Cycle	6 kV
Maximum Switching Surge	17.0 kV
Protective Level @ 500A	
Maximum Discharge Voltage	• 19.5 kV @ 1.5 kA • 20.5 kV @ 3 kA • 22 kV @ 5 kA • 24.5 kV @ 10 kA • 28.5 kV @ 20 kA • 37 kV @ 40 kA
kV Class	15 kV
MCOV	5.1 kV

Dimensions

Width	2.85 in
Weight	3.700 lb.
Height	9.438 in
Length	8.438 in
Dimensions	8.438 in x 2.85 in x 9.438 in

General

Type	Underground Arresters
Grounding Style	36 in Line Lead
Material	Polymer
Material type	Standard
UPC	096359360551

Logistics

Standard Package	1
Pallet Quantity	160

Operational

Maximum Operating Altitude	6000 ft
----------------------------	---------

Product Assets

- [Catalog \[English\]](#)
[Catalog \[English\]](#)
[Installation Manual \[English\]](#)