HUBBELL
Power Systems

35 kV Class Small Interface Elbow Arrester (24.4 kV MCOV)

By Hubbell Power Systems
Catalog # 235ELA30

Small Interface Elbow Arrester, 35kV 24 MCOV



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. C62.11. Section 8.1 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

Specifications

EU RoHS Indicator	No

Current

Duty Cycle	30 kV
Maximum Switching Surge Protective Level @ 500A	74.0 kV
Maximum Discharge Voltage	• 81 kV @ 1.5 kA • 88.5 kV @ 3 kA • 94.5 kV @ 5 kA • 108 kV @ 10 kA • 131.5 kV @ 20 kA • 159 kV @ 40 kA
kV Class	35 kV
MCOV	24.4 kV

Dimensions

Width	3.625 in
Weight	6.500 lb.
Height	14.375 in
Length	10.375 in
Dimensions	10.375 in x 3.625 in x 14.375 in

General

Type	Underground Arresters
Grounding Style	36 in Line Lead
Material	Polymer
Material type	Standard
UPC	096359433439

Logistics

Standard Package	1
Pallet Quantity	64

Operational

Maximum Operating Altitude	6000 ft

Product Assets

Catalog [English]
Catalog [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved